



DIMENSIONS



Unit:mm

PRODUCT

| | |
|---------------------------|--|
| NO. | ZL-LD1-150W |
| LED | Epistar / Cree / Sanan |
| Watts | 150W |
| Lumens | 100lm/w |
| CRI | >80 |
| Color Temperature | 3000K / 4000K / 6000K |
| light body size | 860*330*80mm |
| Driver | Olala |
| AC Input | 220-240V / 50/60Hz |
| Color | black |
| Installation | Street light pole installation Pole installation Wall installation |
| Storage Temperature Range | Temperature:-20°C to +50°C Humidity: 85% |
| Standards of Safety | IEC 60598-1:2014 IEC 60598-1:2014/AMD1:2017 IEC 60598-2-3:2002 IEC 60598-2-3:2002/AMD1:2011 |

Features:

- High-brightness led chip and high-efficiency, anti-glare and economical multi-size design, corresponding to the needs of different place.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- The spectrum does not contain red or ultraviolet light, which protects the eyes.

Application:

Widely used in main roads, secondary roads, branch roads, factories, schools, gardens, city squares, courtyards and other road lighting

