



DIMENSIONS



Unit:mm

PRODUCT

NO.	ZLD-1015-5-10-15W
LED	Cree / Bridgelux / Osram / Epistar
Watts	5W / 10W / 15W
Lumens	85lm/w
CRI	>70
Color Temperature	3000K / 4000K / 6500K
light body size	Φ92*H48mm,other size as below
Beam Angle	60-100 degree
Driver	Olala
AC Input	175-265V
Color	White
Installation	Recessed installation
Storage Temperature Range	Temperature:-20°C to +50°C Humidity: 85%
Standards of Safety	EN 60598-1:2008+A11:2009 EN 60598-2-2:2012

watt	body size(mm)	hole(mm)
5W	Φ92*H48	Φ75
10W	Φ105*H55	Φ85
15W	Φ135*H66	Φ120

Features:

- High-brightness led chip and high-efficiency, anti-glare and economical multi-size design, corresponding to the needs of different place.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- The spectrum does not contain red or ultraviolet light, which protects the eyes.

Application:

Widely used for indoor lighting in shopping malls, offices, factories, hospitals, etc

