



DIMENSIONS

12W




Unit:mm

18W



Unit:mm

15W



Unit:mm

PRODUCT

NO.	ZLP-1001R-12-15-18W
LED	Cree / Bridgelux / Osram / Epistar
Watts	12W / 15W / 18W
Lumens	70-80lm/w
CRI	>70
Color Temperature	3000K / 4000K / 6500K
light body size	Φ165*H18mm, other size as below
Beam Angle	120 degree
Driver	Olala
AC Input	175-265V
Color	White
Installation	Recessed installation
Storage Temperature Range	Temperature: -20°C to +50°C Humidity: 85%
Standards of Safety	EN 60598-1:2008+A11:2009 EN 60598-2-2:2012

watt	body size(mm)	hole(mm)
12W	Φ165*H18	Φ155
15W	Φ185*H18	Φ175
18W	Φ220*H18	Φ205

Features:

- High-brightness led chip and high-efficiency, anti-glare and economical multi-size design, corresponding to the needs of different place.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- The spectrum does not contain red or ultraviolet light, which protects the eyes.

Application:

Widely used in office, hospital, residential and commercial lighting places.

