www.olalalighting.com



DIMENSIONS

18W

| 0 | ١. | ٨ | , |
|---|----|---|---|

| | PRODUCT | |
|------------------------------|------------------------------------|--|
| NO. | ZLP-1011S-18-24W | |
| LED | Cree / Bridgelux / Osram / Epistar | |
| Watts | 18W / 24W | |
| Lumens | 50-60lm/w | |
| CRI | >70 | |
| Color Temperature | 3000K / 4000K / 6500K | |
| light body size | 200*200*33mm,other size as below | |
| Beam Angle | 200 degree | |
| Driver | Olala | |
| AC Input | 175-265V | |
| Color | White | |
| Installation | Recessed installation | |
| Storage Temperature Range | Temperature:-20°C to +50°C | |
| | Humidity: 85% | |
| Standards of Safety | EN 60598-1:2008+A11:2009 | |
| | EN 60598-2-2:2012 | |

| watt | body size(mm) | hole(mm) |
|------|---------------|----------|
| 18W | 200*200*33 | 165*165 |
| 24W | 240*240*40 | 205*205 |

Unit:mm

Features:

- High-brightness led chip and high-efficiency, anti-glare and economical multi-size design, corresponding to the needs of different place.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- Secondary optical design, high light transmittance, unique PC light transmittance makes the light smooth and full.
- The spectrum does not contain red or ultraviolet light, which protects the eyes.

Application:

Widely used in office, hospital, residential and commercial lighting places.